

Apartment Outdoor Station



Features

- · 3.5-inch TFT screen, vivid pictures are on show
- Tempered glass panel, touch buttons.
- Adopt TCP/IP network host, support SNMP network protocol.
- Network security technology, provides stable and safe operating environment.
- Support night vision, voice indication
- · Support card and password to open the door
- · Support visitor leaving audio and video function message
- IP65



Specifications

SystemMain ProcessorEmbedded micro processorOperation SystemEmbedded LINUX OSVideo Compression StandardH.264Input/Approaching Induction1.3 megapixel CMOS cameraBlack LightSupportAutoLight CompensationAutioLight Built-in speakerAudio OutputBuilt-in speakerBidirectional TalkSupport dual-way bidirectional talkDisplayLCD DimensionsResolution320*240
System Embedded LINUX OS Video System H.264 Standard H.264 Input/Approaching Induction 1.3 megapixel CMOS camera Black Light Support Auto Light Compensation Audio Input Support Audio Output Built-in speaker Bidirectional Talk Support dual-way bidirectional talk Display LCD Dimensions 3.5-inch TFT screen
SystemDisplaySystemVideo Compression StandardH.264Input/Approaching Induction1.3 megapixel CMOS cameraInduction1.3 megapixel CMOS cameraBlack LightSupportAutoLight CompensationAudio InputMicrophoneAudio OutputBuilt-in speakerBidirectional TalkSupport dual-way bidirectional talkDisplayLCD Dimensions3.5-inch TFT screen
Standard H.264 Input/Approaching Induction 1.3 megapixel CMOS camera Black Light Support Auto Light Compensation Audio Input Support Audio Output Built-in speaker Bidirectional Talk Support dual-way bidirectional talk Display LCD Dimensions 3.5-inch TFT screen
Standard Input/Approaching Induction 1.3 megapixel CMOS camera Black Light Support Auto Light Compensation Support Audio Input Microphone Audio Output Built-in speaker Bidirectional Talk Support dual-way bidirectional talk Display LCD Dimensions 3.5-inch TFT screen
Video Induction 1.3 megapixel CMOS camera Black Light Support Auto Light Support Compensation Microphone Audio Output Built-in speaker Bidirectional Talk Support dual-way bidirectional talk Display LCD Dimensions 3.5-inch TFT screen
Video Induction Support Black Light Support Auto Light Compensation Support Audio Input Microphone Audio Output Built-in speaker Bidirectional Talk Support dual-way bidirectional talk Display LCD Dimensions 3.5-inch TFT screen
Auto Light Compensation Support Audio Input Microphone Audio Output Built-in speaker Bidirectional Talk Support dual-way bidirectional talk Display LCD Dimensions 3.5-inch TFT screen
Compensation Support Audio Input Microphone Audio Output Built-in speaker Bidirectional Talk Support dual-way bidirectional talk Display LCD Dimensions 3.5-inch TFT screen
Audio Audio Input Microphone Audio Output Built-in speaker Bidirectional Talk Support dual-way bidirectional talk Display LCD Dimensions 3.5-inch TFT screen
Audio Audio Output Built-in speaker Bidirectional Talk Support dual-way bidirectional talk Display LCD Dimensions 3.5-inch TFT screen
Bidirectional Talk Support dual-way bidirectional talk Display LCD Dimensions 3.5-inch TFT screen
Display LCD Dimensions 3.5-inch TFT screen
Display
Resolution 320*240
Operation Input Touch keyboard
Mode Card Built-in IC card induction reader
Approaching Induction Body Approaching IR,1 meter
Alarm Vandal proof Support
No Output Support
Access NC Output Support
Control Door on/off Button Support
Door Status Detect Support
Ethernet 10M/100Mbps Self-adaptive
Network Protocol TCP/IP
Storage Memory 128MB
Power DC 10~15V
Power Consumption Standby ≤1W, work ≤10W
Working $-40^{\circ}\text{C} - +60^{\circ}\text{C}$
Environments 10%-95%RH
Others Water Proof IP65
Dimensions 408.0mm*150.0mm*46.4mm (L*W*T);
Weight 1.6Kg;
Installation Method Flush mounted



Dimensions

Dimensions

150.0 mm





